


Specifications

MODELS	DPL™-25S		DPL™-30S		DPL™-35S	
MEASUREMENTS	US	Metric	US	Metric	US	Metric
Working height*	31 ft 4 in	9.70 m	36 ft	11.14 m	40 ft 10 in	12.62 m
Platform height	25 ft 4 in	7.70 m	30 ft	9.14 m	34 ft 10 in	10.62 m
Height - stowed	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
Length - stowed	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m
Width	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m
PRODUCTIVITY						
Lift capacity: ANSI/CSA/CE	750 lbs	340 kg	750 lbs	340 kg	600 lbs	272 kg
ANSI/CSA						
Outrigger footprint:						
A length	6 ft 10 in	2.08 m	7 ft 2 in	2.18 m	7 ft 2 in	2.18 m
B width	4 ft 8.5 in	1.44 m	5 ft 8 in	1.73 m	5 ft 8 in	1.73 m
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m
CE						
Outrigger footprint:						
A length	6 ft 10 in	2.08 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in	2.19 m
B width	4 ft 8.5 in	1.44 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in	1.75 m
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m
Platform length	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
Platform width	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m
POWER						
Power source: AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz					
DC models	12 V					
WEIGHT**						
ANSI (AC)/CSA	1,371 lbs	622 kg	1,474 lbs	669 kg	1,574 lbs	714 kg
ANSI (DC)/CSA	1,481 lbs	672 kg	1,584 lbs	718 kg	1,684 lbs	764 kg
CE (AC)	1,371 lbs	622 kg	1,474 lbs	669 kg	1,645 lbs	746 kg
CE (DC)	1,481 lbs	672 kg	1,584 lbs	718 kg	1,755 lbs	796 kg
STANDARDS COMPLIANCE ANSI A92.3, CSA B354.1, EN 280, AS 1418.10						



* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Weight will vary depending on options and/or country standards

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM

- 6 ft x 2 x 3.5 in (1.83 m x .70 m)

POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V / 190 amp battery

STANDARD FEATURES

MEASUREMENTS

DPL™-25S

- 31 ft 4 in (9.55 m) working height
- 25 ft 4 in (7.72 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lb (340 kg) lift capacity

DPL™-30S

- 36 ft (10.97 m) working height
- 30 ft (9.14 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lb (340 kg) lift capacity

DPL™-35S

- 40 ft 10 in (12.62 m) working height
- 34 ft 10 in (10.62 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 600 lb (272 kg) lift capacity

PRODUCTIVITY

- Large platform with room for 1-2 workers
- Auxiliary platform lowering
- Most rigid mast in the industry
- Durable base system
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Patented outrigger interlock system
- Outrigger storage sockets
- Swivel-lock caster
- Tie down attachment points
- Forklift pocket access on all sides
- Angled entry ladder
- LED lights confirm proper set-up of outriggers
- Winch attachment points
- Locking key switch

POWER

- DC models include a 15 amp charging system with 110V / 50-60 Hz or 220V / 50-60 Hz input voltage



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Operational warning light and descent alarm package (mandatory for CE and AUS)
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V 190 Amp battery

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **+1 (425) 881-1800**
Toll Free in USA/Canada **+1 (800) 536-1800**
Fax +1 (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
UK

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: AWP-InfoEurope@terex.com

Distributed By:

Effective Date: April, 2011. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Brand. © 2011 Terex Corporation.