


Specifications

MODELS	IWP™-20S		IWP™-25S		IWP™-30S	
	US	Metric	US	Metric	US	Metric
Working height*	26 ft 6 in	8.24 m	30 ft 5 in	9.44 m	35 ft 6 in	11 m
Platform height	20 ft 6 in	6.24 m	24 ft 5 in	7.44 m	29 ft 6 in	9 m
A Horizontal outreach**	2 ft 2 in	.66 m	—	—	—	—
B Height - stowed:						
fully lowered	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m
base raised	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
C Length	5 ft	1.52 m	5 ft	1.52 m	5 ft	1.52 m
D Width - standard base	2 ft 8 in	.81 m	2 ft 8 in	.81 m	—	—
wide base	—	—	—	—	3 ft 4 in	1.02 m
Corner access***	6 in	.15 m	6 in	.15 m	7 in	.18 m



PRODUCTIVITY						
Lift capacity: ANSI/CE/CSA	350 lbs	159 kg	350 lbs	159 kg	350 lbs	159 kg
ANSI/CE with outreach option	300 lbs	136 kg	—	—	—	—
Platform Dimensions (l/w/h)						
Standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated standard	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm
Gated narrow	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm
Front entry gated narrow	20/26/44.75 in	51/66/114 cm	20/26/44.75 in	51/66/114 cm	20/26/44.75 in	51/66/114 cm
Front/side entry extra-large**	30/28/44.75 in	76/71/114 cm	30/28/44.75 in	76/71/114 cm	30/28/44.75 in	76/71/114 cm
Standard fiberglass**	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm

POWER	
AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V / 110 V / 60 Hz or 110/230 Hz worldwide model

WEIGHT****						
Standard base						
ANSI (AC)/CSA	1,245 lbs	565 kg	1,290 lbs	585 kg	—	—
ANSI (DC)/CSA	1,345 lbs	610 kg	1,390 lbs	630 kg	—	—
CE (AC)	1,245 lbs	565 kg	1,290 lbs	585 kg	—	—
CE (DC)	1,345 lbs	610 kg	1,390 lbs	630 kg	—	—
Standard base with outreach option						
ANSI (AC)	1,350 lbs	612 kg	—	—	—	—
ANSI (DC)	1,450 lbs	658 kg	—	—	—	—
CE (AC)	1,350 lbs	612 kg	—	—	—	—
CE (DC)	1,450 lbs	658 kg	—	—	—	—
Wide base						
ANSI (AC)/CSA	—	—	—	—	1,430 lbs	649 kg
ANSI (DC)/CSA	—	—	—	—	1,530 lbs	694 kg
CE (AC)	—	—	—	—	1,430 lbs	649 kg
CE (DC)	—	—	—	—	1,530 lbs	694 kg

STANDARDS COMPLIANCE	ANSI A92.3, CSA B354.1, EN 280, AS 1418.10
----------------------	--

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Fiberglass platforms are not available with the outreach option.
 *** Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.
 **** Weight will vary depending on options and/or country standards.

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

PLATFORM

- Sliding mid-rail standard platform
- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform

POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz worldwide model
- Power assist option*

BASE

- Standard base (IWP-20S and 25S only)
- Wide base (IWP-30 only)

STANDARD FEATURES

MEASUREMENTS

IWP™-20S

- 26 ft 6 in (8.24 m) working height
- 20 ft 6 in (6.24 m) platform height
- 2 ft 8 in (.81 m) standard base width
- Outreach option adds 2 ft 2 in (.66 m) of horizontal reach
- Up to 350 lb (159 kg) lift capacity

IWP™-25S

- 30 ft 5 in (9.44 m) working height
- 24 ft 5 in (7.44 m) platform height
- 2 ft 8 in (.81 m) standard base width
- Up to 350 lb (159 kg) lift capacity

IWP™-30S

- 35 ft 6 in (11 m) working height
- 29 ft 6 in (9 m) platform height
- 3 ft 4 in (1.02 m) wide base width
- Up to 350 lb (159 kg) lift capacity

PRODUCTIVITY

- Sliding mid-rail standard platform
- Auxiliary platform lowering
- Most rigid mast in the industry
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks

POWER

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform (not available with outreach)
- Outreach option (IWP-20S only)
- Operational warning light and descent alarm package (mandatory for CE and AUS)
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

POWER

- Power wheel assist with dual battery package*
- Dual battery package

* Adds 12.5 in (.32 m) to unit length and 285 lbs (129 kg) to unit weight

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **+1 (425) 881-1800**
Toll Free in USA/Canada **+1 (800) 536-1800**
Fax +1 (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
UK

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: AWP-InfoEurope@terex.com

Distributed By:

Effective Date: April, 2011. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries and all rights are reserved. Terex is a Registered Trademark of Terex Corporation in the U.S.A. and many other countries. Genie is a Registered Trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Brand. © 2011 Terex Corporation.